National Institute of Standards and Technology

Nuclear Data Verification and Standardization Program

PROGRESS REPORT

USNDP Meeting **Brookhaven National Laboratory November 18, 2011**

THE NEUTRON CROSS SECTION STANDARDS

Reaction	Energy Range	
H(n,n)	1 keV to 20 MeV	
3 He(n,p)	thermal to 50 keV	
⁶ Li(n,t)	thermal to 1 MeV	
$^{10}\mathrm{B}(\mathrm{n,}\alpha)$	thermal to 1 MeV	
$^{10}\mathrm{B}(\mathrm{n,}\alpha_{1}\gamma)$	thermal to 1 MeV	
C(n,n)	thermal to 1.8 MeV	
197 Au(n, γ)	thermal, 0.2 to 2.5 MeV	
²³⁵ U(n,f)	thermal, 0.15 to 200 MeV	
²³⁸ U(n,f)	2 to 200 MeV	



Nuclear Structure Activities:

- •None are supported by DOE funding.
- •A modest effort, largely experimental, (about 1 FTE) in structure and decay studies is supported by NIST. The effort is in support of needs for radioactivity and radiopharmaceutical applications.
- •Nuclear Reaction Activities: Neutron Cross Section Standards Measurements

H(n,n)H Angular Distribution Work

•This work was initiated to resolve problems with the hydrogen database used for the ENDF/B-VI hydrogen evaluation. We previously made measurements at 10 and 14.9 MeV at laboratory proton recoil angles of 0 degrees, \pm 12 degrees (one on each side of the beam direction), \pm 24 degrees, \pm 36 degrees, \pm 48 and \pm 60 degrees at the Ohio University accelerator facility. The data were obtained by detecting the recoil proton.

(collaboration of NIST, Ohio University, LANL and the University of Guelma)

H(n,n)H Angular Distribution Work (cont.)

- •In order to make measurements at smaller scattering angles where only one experiment with large uncertainties has been done, we started an experiment where the primary objective is detection of the scattered neutron instead of the scattered proton.
- •The work is being done at the Ohio University accelerator facility. Measurements have been made at laboratory neutron scattering angles from 20 degrees to 65 degrees in 5 degree steps for 14.9 MeV incident neutrons but not at the desired accuracy. The plan is to extend the range so that data are obtained from 15 to 70 degrees.
- •For these measurements, it is essential to accurately determine the efficiency of the neutron detector.

(collaboration of NIST, Ohio University, LANL and the University of Guelma)

H(n,n)H Angular Distribution Work (cont.)

- •For neutron energies above 9 MeV, a technique using reactions where the projectile and target are identical will be used. Because they are identical, the angular distribution **must** be symmetrical in the CMS. Thus, for a bombarding energy such that the backward portion of the angular distribution falls in the energy range below 9 MeV where the efficiencies are well known, we can reduce these data to obtain cross sections for a given group in the backward hemisphere. Reflecting these data gives us the cross sections in the forward hemisphere which are the same. The center-of mass cross section would then be converted to lab cross sections. Analysis of the measured counts at the appropriate angles can then give us the efficiency for the 14 MeV neutron energy range.
- •A study of possible targets indicated that the ⁶Li(⁶Li,n)¹¹C reaction is the best for our use. Neutrons could be used from the ground and two excited states for ¹¹C to give the desired neutron energies.
- •Work has been done to try to evaporate a suitable target using lithium metal and then LiCl. Various backings and surface coatings were used with limited success. This is an ongoing project

(collaboration of NIST, Ohio University, LANL and the University of Guelma)

Nuclear Reaction Activities: Neutron Cross Section Standards—Measurements

⁶Li(n,t) Work

•Measurements have been completed of the ⁶Li(n,t) cross section standard at ~ 4 meV neutron energy. These are the first direct and absolute measurements of this cross sections in this neutron energy range using monoenergetic neutrons. A primary effort has been focused on measuring the neutron fluence accurately. That has now been determined with an uncertainty of less than 0.05%.

The limitation on the accuracy of the ⁶Li(n,t) cross section measurement is the mass uncertainty of the ⁶Li target. The present mass uncertainty is about 0.25%. Further studies are being made to compare the mass with the value obtained when it was characterized a number of years ago. It is expected that a total uncertainty less than 0.3% for the cross section can be obtained from this experiment.

(collaboration with the University of Tennessee and Tulane University)

$^{10}B(n,\alpha)$ Work

•The same basic experimental setup being used for the NIST collaborative measurements of the $^6\text{Li}(n,t)$ cross section at ~ 4 meV will be used to measure the $^{10}\text{B}(n,\alpha)$ cross section also. We have noted a problem with loss of ^{10}B from evaporated deposits. Plans for making $10\text{B}(n,\alpha)$ measurements at low neutron energies are being delayed while work is being done to investigate these losses

Nuclear Reaction Activities: Neutron Cross Section Standards –Fluence Data

Fluence Determination Work

- •Improvements in the determination of the source strength for NBS-I continue. This work will have an impact on cross section measurements that have used this source as a standard and any future measurements made using this source.
- •Additional work continues on an independent determination of the neutron intensity of NBS-I for comparison with the established value obtained from manganese sulfate bath measurements and calculations. The new work is in principle only limited in accuracy by the uncertainty in nu-bar of ²⁵²Cf, 0.12%. Preliminary results indicate a 1.7 % difference with a 0.9 % uncertainty for this determination compared with the NBS-I value. It is expected that a 0.3% uncertainty in the calibration will be possible.

Nuclear Reaction Activities: Neutron Cross Section Standards – Evaluations

- •We have written a contribution for a special issue of Metrologia that is devoted to neutron metrology. Our section is on neutron cross section standards-their history, how they are measured, evaluated and used. It was just recently published.
- •Improvements continue to be made to the experimental data in the standards database as a result of NIST involvement or encouragement

IAEA Consultants' Work

- •In order to improve the standards on a continuing basis, an IAEA Nuclear Data Development Project "Maintenance of the Neutron Cross Section Standards" was initiated through NIST efforts.
 - •This project will pursue improvements in the experimental database, consider additional standards, maintain evaluation codes and periodically update the standards so they are available for new versions of data libraries
 - •Two Consultants' Meetings have been held for this Data Development Project. Both meetings were chaired by the NIST participant.

- •Updating of the standards database.
 - •The experiments completed or underway since the completion of the standards evaluation were reviewed.
 - •The experiments suggest improvements have been made for the H(n,n), Li(n,t), 10 B(n, α), Au(n, γ), and 238 U(n, γ) cross sections.
 - •There are inconsistencies for the ³He(n,p), C(n,n), ²³⁸U(n,f) and ²³⁹Pu(n,f) cross sections.

•Neutron spectra

• No new measurements have been made of the 252 Cf spontaneous fission neutron spectrum. There are new measurements of the 235 U(n_{th},f) neutron spectrum made by Kornilov (Hambsch) et al. and Vorobyev et al.

- •Neutron spectra (cont.)
 - The most recent measurements of the 235 U(n_{th},f) neutron spectrum have been made with a 252 Cf source located outside the beam. Thus ratio measurements of these spectra were obtained.
 - For the standards evaluation the GMA code was used to properly evaluate ratio data. Then there was an impact on both quantities in the ratio.
 - It seemed reasonable to use the GMA code for a simultaneous evaluation of these two fission spectra. This was done and it included smoothing using a model. There were some problems with the preliminary results of the work. There was a critical review of the process with many helpful suggestions for the next set of calculations.

- •Reference cross sections for measurements of prompt gamma-ray production cross sections. (cont.)
 - •Many nuclides and reactions were considered
 - natTi with large yields of two gamma-lines, 984 keV from ⁴⁸Ti(n,n') and 160 keV from ⁴⁸Ti(n,2n) and ⁴⁷Ti(n,n') reactions appears to be the most suitable for use as a reference cross section. More work needs to be done to improve the database.

- •Au(n, γ) reference cross section for capture cross section measurements for astrophysics (below the standards energy region).
 - •Due to the evaluation process used for the standards evaluation, data for the $Au(n,\gamma)$ cross section were obtained for energies below 200 keV.
 - •These results are consistently higher than the Ratynski evaluation (by about 5-7% from 15 to 25 keV) which is used in astrophysics applications.
 - •The Ratynski evaluation relies on Macklin capture data and Ratynski-Käppeler Karlsruhe pseudo-Maxwellian capture data.
 - •The standards evaluation uses a large database of various types of data.
 - •New data by Wallner et al., Lederer et al., Borella et al. and Lampoudis et al. support our evaluation.
 - •There are new measurements by Feinberg et al. that in one case support and in another case disagree with our evaluation. That work is very preliminary.

Other Work

- •The NIST National Repository for Fissionable Isotope Mass Standards continues to acquire and monitor samples. A number of laboratories have borrowed samples from the Repository.
- •NIST had two members on the International Program Committee for the International Symposium on Radiation Dosimetry, ISRD-14 (2011). The members of the ISRD use cross section data to determine the fluence in reactor aplications. The ENDF standards are part of the data used. A session on "nuclear data for dosimetry" and a workshop on "cross sections and nuclear data" were organized by NIST. Also we gave an invited talk at the Symposium, "New Work on Updating and Extending the Nuclear Data Standards", which describes the activities of the Nuclear Data Development Project, "Maintenance of the Neutron Cross Section Standards".

Staff Data (not including structure work of 1 FTE, entirely supported by NIST)

STAFF	FTE	HEADS	FTE (USNDP)
Permanent	0.3	1	0.15
Temporary	0.2	1	0
Professional			
Contractors	1.0	2	0.4
Total	1.5	4	0.55

Recommendations

•Though the international evaluation of the standards has been completed, maintaining an active program of measurements and evaluation activities is essential for improvement of the standards. We maintain a modest experimental program and encourage work on the standards through collaborations and independent research. Some of the evaluation activities are being done under the IAEA Nuclear Data Development Project "Maintenance of the Neutron Cross Section Standards". This project will pursue improvements in the experimental database, consider additional standards, maintain evaluation codes and periodically update the standards so they are available for new versions of nuclear data libraries.