



Monte Carlo Benchmark Calculations with Revised $^{235,238}\text{U}$ Evaluations

A. C. (Skip) Kahler
Bettis Atomic Power Laboratory
Bechtel Bettis, Inc.

Presented at the November 4 - 6, 2003
Cross Section Evaluation Working Group (CSEWG) Meeting
held at
Brookhaven National Laboratory



- Bettis has performed continuous energy Monte Carlo eigenvalue calculations for a variety of geometrically simple uranium fueled benchmarks with ENDF/B-VI.8, JEFF-3.0, JENDL-3.3 or alternative (BRC3, KAPL, LANL, Maslov, ORNL) $^{235,238}\text{U}$ data sets.
 - ENDF/B, JEFF-3.0 and JENDL-3.3 results were recently published in the NS&E ICSBEP special edition, Nucl. Sci. Eng., 145, 213 (2003).
- Eigenvalues presented on subsequent slides are calculated from tracking 50 million neutron histories in ten independent 5 million history jobs.
 - The 95% eigenvalue confidence interval, determined from the variance in the ten independent eigenvalue estimates, is typically less than $0.0005 \Delta k$ (i.e., roughly the size of the plot symbol).



- A majority of these calculations use models derived from ICSBEP evaluations, as follows:
 - HEU-SOL-THERM
 - 9 evaluations, 31 critical configurations plus two ORNL experiments (L5, L6) not yet in ICSBEP.
 - 4 evaluations (8 critical configurations) include a H₂O reflector.
 - LEU-COMP-THERM
 - 8 evaluations, 59 critical configurations.
 - 2 evaluations (17 critical configurations) contain metallic reflectors.
 - LEU-SOL-THERM
 - 9 evaluations, 39 critical configurations
 - 4 evaluations (19 critical configurations) include a H₂O reflector.




Selected HEU-SOL-THERM ICSBEP Benchmarks

Benchmark	Description
HEU-SOL-THERM-001 (encompass "RF#")	Unreflected cylinders (~28cm, ~33cm and ~51cm diameter) containing uranyl nitrate.
HEU-SOL-THERM-009 (Case 3 = ORNL L7)	Water reflected spheres (6.4-liter) containing uranium oxyfluoride.
HEU-SOL-THERM-010	Water reflected sphere (9.7-liter) containing uranium oxyfluoride.
HEU-SOL-THERM-011	Water reflected spheres (17-liter) containing uranium oxyfluoride.
HEU-SOL-THERM-012 (ORNL L10)	Water reflected sphere (91-liter) containing uranium oxyfluoride.
HEU-SOL-THERM-013 (ORNL1)	Unreflected sphere (174-liter) containing uranium nitrate.
HEU-SOL-THERM-032 (ORNL10)	Unreflected sphere (48-inch diameter) containing uranyl nitrate.
HEU-SOL-THERM-042 (encompass ORNL12 through ORNL23)	Unreflected cylinders (~77cm and ~137cm diameter) containing uranium nitrate.
HEU-SOL-THERM-043 (Cases 2 and 3 are ORNL L8 and ORNL L9)	Unreflected spheres (17-liter, 91-liter and 174-liter) containing uranium oxyfluoride solution.
ORNL L5, L6	Unreflected cylinders (13cm diameter) of uranium oxyfluoride. Low $H/^{235}\text{U}$ ratios of 27 and 44 lead to large leakage.




HEU-SOL-THERM Eigenvalues





HEU-SOL-THERM Eigenvalues





HEU-SOL-THERM Observations

- The historical trend in calculated eigenvalue as a function of Above-Thermal Leakage Fraction (ATLF) is statistically insignificant in the latest evaluated cross section libraries.
 - $k_{\text{calc}}(\text{ATLF}) = 1.0002(18)^{(a)} - 0.0028(52) * \text{ATLF}$ (ENDF/B-VI.8)
 - $k_{\text{calc}}(\text{ATLF}) = 0.9992(18) + 0.0016(52) * \text{ATLF}$ (JEFF-3.0)
 - $k_{\text{calc}}(\text{ATLF}) = 1.0013(18) - 0.0027(52) * \text{ATLF}$ (JENDL-3.3)
- The ATLF trend reappears when the latest LANL $^{235,238}\text{U}$ data sets are used. The revised ^{235}U fission spectrum is the primary cause for this reappearance.
 - $k_{\text{calc}}(\text{ATLF}) = 1.0001(20) - 0.0087(54) * \text{ATLF}$
 - In the absence of further modifications to eliminate this new trend, the User community will not perceive the latest ^{235}U evaluation to be an improvement over data sets that are already available.
- (a) Read 1.0002(18) as 1.0002 ± 0.0018 , where 0.0018 is a two sigma uncertainty on the preceding value.



Selected LEU-COMP-THERM ICSBEP Benchmarks


Benchmark	Description
LEU-COMP-THERM-002	Water moderated and reflected U(4.31)O ₂ 1.415 cm OD fuel rods in 2.54 cm square pitched arrays. Cases 4 and 5 consist of three clusters of 15 x 8 and 13 x 8 rods, respectively.
LEU-COMP-THERM-006	Water moderated and reflected U(2.60)O ₂ 1.417 cm OD fuel rods in 1.85 cm to 2.29 cm square pitched 15x15 to 21x21 arrays.
LEU-COMP-THERM-007	Water moderated and reflected U(4.74)O ₂ 0.94 cm OD fuel rods in square and triangular arrays (cases 1 through 7). Pitch varies from 1.26 cm to 2.52 cm.
LEU-COMP-THERM-010	Water moderated U(4.31)O ₂ 1.415 cm OD fuel rods in 2.54 cm square pitched arrays reflected by two lead, uranium or steel walls at varying distances from the rod clusters. Cases 1 through 13 (mostly 13 x 8 rod clusters with a rod pitch of 2.54 cm) analyzed.
LEU-COMP-THERM-022	Water moderated and reflected U(10)O ₂ 0.51 cm OD fuel rods in triangular pitched (0.7 cm to 1.85 cm) arrays.
LEU-COMP-THERM-024	Water moderated and reflected U(10)O ₂ 0.51 cm OD fuel rods in square pitched (0.62 cm and 0.88 cm) arrays.
LEU-COMP-THERM-027	Water moderated and lead reflected U(4.74)O ₂ 0.94 cm OD fuel rod arrays (1.60 cm square pitch and variable distance to the lead reflector).
LEU-COMP-THERM-039	Water moderated and reflected U(4.74)O ₂ 0.94 cm OD fuel rods in square 1.26 cm pitch, 21x21 or 22x22 arrays. Arrays contain 1 in <i>n</i> missing rods (i.e., water holes), for <i>n</i> =5,4,3 and 2.



Selected LEU-SOL-THERM ICSBEP Benchmarks


Benchmark	Description
LEU-SOL-THERM-001	"SHEBA-II". An unreflected $\text{UO}_2\text{F}_2 + \text{H}_2\text{O}$ cylindrical (~20 inch diameter) assembly.
LEU-SOL-THERM-002	174-liter spheres of low enriched (4.9%) uranium oxyfluoride solutions. Case 1 is a water reflected solution, case 2 is unreflected.
LEU-SOL-THERM-003	Bare spheres of 10% enriched uranyl nitrate water solutions. Cases 3, 6 and 9 are full spheres with increasing H-to- ^{235}U ratio.
LEU-SOL-THERM-004	STACY; Water reflected, 10% enriched uranyl nitrate solution in a 60cm diameter cylindrical tank. Seven cases with varying gU/liter.
LEU-SOL-THERM-007	STACY; Unreflected, 10% enriched uranyl nitrate solution in a 60cm diameter cylindrical tank. Five cases with varying gU/liter.
LEU-SOL-THERM-016	STACY; Water reflected, 10% enriched uranyl nitrate solution in a rectangular (slab, ~28cm x ~69cm) tank. Seven cases with varying gU/liter.
LEU-SOL-THERM-017	STACY; Unreflected, 10% enriched uranyl nitrate solution in a rectangular (slab, ~28cm x ~69cm) tank. Six cases with varying gU/liter.
LEU-SOL-THERM-020	STACY; Water reflected, 10% enriched uranyl nitrate solution in an 80cm diameter cylindrical tank. Four cases with varying gU/liter.
LEU-SOL-THERM-021	STACY; Unreflected, 10% enriched uranyl nitrate solution in an 80cm diameter cylindrical tank. Four cases with varying gU/liter.

LEU-COMP-THERM Eigenvalues






LEU-xxx-THERM Eigenvalues with ENDF/B-VI.8 Cross Sections



CSEWG 2003
Skip Kahler




LEU-xxx-THERM Eigenvalues with ENDF/B-VI.8 Cross Sections




CSEWG 2003
Skip Kahler



LEU-xxx-THERM Eigenvalues with ENDF/B-VI.8, JEFF-3.0 and JENDL-3.3 Cross Sections




LEU-COMP-THERM Eigenvalues with Selected ^{238}U Data Sets







LEU-COMP-THERM Eigenvalues with Selected ^{238}U Data Sets



LEU-COMP-THERM Eigenvalues with Selected ^{238}U Data Sets



LEU-COMP-THERM Eigenvalues with Selected ^{238}U Data Sets





LEU-COMP-THERM Observations

- LEU-COMP-THERM eigenvalues are generally low, with a decreasing eigenvalue trend observed as a function of Above Thermal Fission Fraction, ATFF or as a function of ^{238}U absorption fraction.
 - New data sets proposed by BRC03, LANL, Maslov and ORNL all yield larger, but still less than unity, LCT benchmark eigenvalues.
 - The BRC03 and LANL data sets also reduce the magnitude of the eigenvalue trend with ^{238}U capture fraction, but do not eliminate it. Maslov and ORNL changes are too small to draw such a conclusion.
 - Calculations with the KAPL v223 data set, not shown on the previous plots, exhibit an average eigenvalue decrease of $\sim 0.05\%$, suggesting that the continuum inelastic scattering representation is not a significant contributor to these deficiencies.



Final Observations

- Current (ENDF/B-VI.8, JEFF-3.0, JENDL-3.3) libraries generally perform well for ^{235}U solution systems.
 - HEU-SOL-THERM eigenvalues are virtually unity with no underlying eigenvalue trend as a function of Above-Thermal Leakage Fraction (ATLF).
 - 33 ENDF/B-VI.8 eigenvalues range from 0.9931 to 1.0063, with an average of $0.9994 \pm 0.0010 \pm 0.0057$ (0.0010 and 0.0057 are 95% confidence intervals for the average and for the population, respectively).
 - LEU-SOL-THERM benchmarks, whose ATLF values range from ~ 0.06 to ~ 0.24 , also exhibit near unity eigenvalues
 - 39 ENDF/B-VI.8 eigenvalues range from 0.9916 to 1.0103, with an average of $0.9994 \pm 0.0011 \pm 0.0066$ (0.0011 and 0.0066 are 95% confidence intervals for the average and for the population, respectively).
- Future data set revisions should strive to maintain these excellent results.